

## INSTALLATION INSTRUCTIONS

### LID ORGANIZER FOR GL1800

5837

#### THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

- WARNING** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.
- CAUTION** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.
- NOTICE** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

#### ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- |   |               |   |                                       |
|---|---------------|---|---------------------------------------|
| 1 | Lid Organizer | 1 | Snap Bar A (middle support - shorter) |
| 2 | Snap Tab B    | 1 | Snap Bar B (bottom support - longer)  |

#### YOU WILL ALSO NEED:

Philips Screw Driver

**NOTICE** THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

**NOTICE** THE RECOMMENDED LOAD CAPACITY IS **2.5 POUNDS**. KURYAKYN IS NOT RESPONSIBLE FOR ANY DAMAGE, LOSS, OR INJURY CAUSED BY EXCEEDING THE RECOMMENDED LOAD CAPACITY.

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

**STEP 2** Refer to PIC 2 and 3. Locate provided Snap Tab B. **ONE AT A TIME** remove a trunk lid screw and washer. Fasten a snap tab to the inside of the lid using the hardware that was removed. Repeat process until all snap tabs have been installed. Fully tighten hardware.



## INSTALLATION INSTRUCTIONS

### LID ORGANIZER FOR GL1800

5837

-CONTINUED-

- STEP 3** Refer to FIG 1. Locate provided lid organizer, Snap Bar A and Snap Bar B.
- STEP 4** On the back side of the lid organizer, slide bar A through the middle sleeve, and slide bar B through the bottom two (2) sleeves.
- STEP 5** Starting with the middle bar, **ONE AT A TIME** remove a trunk lid screw on either side of the trunk. Fasten one side of the snap bar to the inside of the lid using the hardware that was removed. Repeat the process until both bars are fastened to the trunk lid.
- STEP 6** Fasten the top two (2) snaps on the back of the lid organizer to the installed snap tabs.

FIG 1



FINAL



**NOTICE**

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.