



## EXTENDED ISO™-THROTTLE BOSS™ 6242

**FITS: ALL KÜRYAKYN ISO-GRIPS AND ISO-FLAME GRIPS INCLUDING P/N 6183 FOR GL1800, (1/4" LONGER THAN STANDARD ISO-THROTTLE BOSS)**

### PARTS INCLUDED

- 1 Extended ISO-Throttle Boss
- 4 4-40 x 9/16" Socket Head Cap Screw (SHCS)
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

### THANK YOU FOR CHOOSING KÜRYAKYN!

**NOTE** It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

### TOOLS SUGGESTED

3/32" Allen Wrench

### PROCEDURE

**STEP 1** Remove the end cap from the ISO-Grip.

**STEP 2** Place the Extended ISO-Throttle Boss between the grip body, and the trim ring. Loosely re-install the end cap with the Extended ISO-Throttle-Boss in place, using the included longer socket head screws.

**STEP 3** Position the Extended ISO-Throttle Boss where it will be the most comfortable for you at cruising speeds.

**STEP 4** Tighten the mounting screws

*Ride On!*