



STILETTO END CAPS for ISO GRIPS

6249

PARTS INCLUDED

- 2 Stiletto End Caps
- 8 #4-40 X 9/16" Socket Head Cap Screws — Stainless Steel
- 8 #4-40 x 3/4" Socket Head Cap Screws — Stainless Steel
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.
- STEP 2** Remove the original ends from the ISO-Grips.
- STEP 3** Remove the trim rings from the original end caps and place them on the new Stiletto End Caps.
- STEP 4** Install a Stiletto End Cap and trim ring assembly on each ISO-Grip using four #4-40 x 9/16" Socket Head Cap Screws. For ISO-Grips equipped with an ISO Throttle Boss, we have included longer (3/4") #4-40 Socket Head Cap Screws.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

Ride On!