



**CONTOURED ISO THROTTLE BOSS 6309**

**FITS LEFT SIDE**

**FITS: ISO, ISO-FLAME AND TRANSFORMER GRIPS**

**PARTS INCLUDED**

- 1 Contoured ISO-Throttle Boss
- 4 4-40 x 9/16" Socket Head Cap Screws (SHCS)
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

**THANK YOU FOR CHOOSING KÜRYAKYN!**

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**TOOLS SUGGESTED**

Set of Hex Wrenches

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**PROCEDURE**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

**STEP 2** Remove the 4 screws securing the end cap to the ISO-Grip. Remove the end cap and trim ring.

**STEP 3** Place the Contoured ISO-Throttle Boss between the grip body and the trim ring. Loosely re-install the end cap with the Throttle-Boss in place using the included 4-40 x 9/16" SHCS.

**STEP 4** Position the ISO-Throttle Boss where it will be the most comfortable for you at cruising speeds.

**STEP 5** Tighten the mounting screws.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

**CAUTION!** Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

*Ride On!*