



CONTOURED ISO-THROTTLE BOSS 6310

FITS: KURYAKYN ISO GRIPS FOR GL1800 WITH HEATED GRIPS (P/N 6183)

PARTS INCLUDED

- 1 Contoured ISO-Throttle Boss
- 4 4-40 x 9/16" Socket Head Cap Screws (SHCS)
- 1 Installation Instruction

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Remove the 4 screws securing the end cap to the ISO-Grip. Remove the end cap and trim ring.

STEP 2 Place the Contoured ISO-Throttle Boss against the grip body (PIC 1). Loosely re-install the end cap with the Throttle-Boss in place using the included 4-40 x 9/16" SHCS.

STEP 3 Position the ISO-Throttle Boss where it will be the most comfortable for you at cruising speeds.

STEP 4 Tighten the mounting screws and check for proper throttle operation

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.



CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

Ride On!