



CONTOURED ISO THROTTLE BOSS/BLACK 6318

PARTS INCLUDED

- 1 Contoured ISO-Throttle Boss-Black
- 4 #4-40 x 9/16" Socket Head Cap Screws (SHCS)
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.

| | |
|----------------|---|
| NOTICE | This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality. |
| CAUTION | This indication alerts you to the fact that ignoring the contents described herein can result in potential injury. |


| | |
|---------------|---|
| NOTICE | IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM. |
|---------------|---|

TOOLS SUGGESTED

Set of Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.
- STEP 2** Remove the 4 screws securing the end cap to the ISO-Grip. Remove the end cap and trimring.
- STEP 3** Place the Contoured ISO-Throttle Boss between the grip body and the trim ring (PIC 1). Loosely re-install the end cap with the Throttle-Boss in place using the included #4-40 x 9/16" SHCS.
- STEP 4** Position the ISO-Throttle Boss where it will be the most comfortable for you at cruising speeds. Tighten the screws.



| | |
|----------------|--|
| CAUTION | Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding. |
|----------------|--|

| | |
|---------------|---|
| NOTICE | It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not provide warranty coverage on products or components lost due to improper installation or lack of maintenance. Periodic inspection and maintenance are required on all fasteners. |
|---------------|---|

Ride On!