



GRIP END WEIGHTS—BLACK

6339

PARTS INCLUDED

- 2 Black Bar End Weights
- 1 Hardware Kit Containing
 - 8 #4-40 x 9/16" Socket Head Cap Screw
 - 8 #4-40 x 3/4" Socket Head Cap Screw
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

NOTE: ISO Grips for GL 1800 with heated grips (Kuryakyn P/N 6183) requires the separate purchase of smooth accent rings (P/N 6264-6266) for proper installation.

STEP 2 Remove the four-socket head cap screws on the end cap from your all ready installed Kuryakyn grip. Keep the trim ring because you will reuse it.

STEP 3 Place the trim ring on the new bar end weight and place it on to the grip. Secure it with four #4-40 x 9/16" Socket Head Cap Screw.

STEP 4 Repeat steps 2 and 3 for opposite side installation.

NOTE: The longer (8) #4-40 x 3/4" Socket Head Cap Screws are for use when installing the new bar end weights with a Kuryakyn throttle boss, P/N 6299, P/N 6250, P/N 6253, P/N 6309, P/N 6319 or P/N 6318.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

Ride On!