

INSTALLATION INSTRUCTIONS

MESH GAS CAP, VENTED, SATIN BLACK

6549

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Mesh Gas Cap

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE SATIN BLACK PARTS WILL BE THE SAME.

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove the existing gas cap.

Refer to PIC 1. Make note of the existing gasket on the gas cap.

STEP 3 Refer to PIC 2 and 3. Locate Mesh Gas Cap. Remove the two gaskets from the provided cap.

STEP 4 Refer to PIC 4 through 7, on page 2. Determine the correct gasket for the application. Only install the appropriate gasket for the application. DO NOT double up the gaskets.

STEP 5 Install the Mesh Gas Cap with the correct gasket. Ensure that the Cap is properly threaded into the bung. Turn the Cap clockwise until it is aligned to your liking. The cap will seal in the bung and then “ratchet” until it is aligned.

WARNING SOME MOTORCYCLES HAVE REPLACEMENT GAS TANKS.

ENSURE THAT YOU PAY CLOSE ATTENTION TO THE GASKET THAT IS ON THE CAP YOU ARE REPLACING. USE THE CORRECT REPLACEMENT GASKET.

FAILURE TO DO SO MAY RESULT IN A FUEL LEAK, CREATING A FIRE HAZARD, CAUSING LOSS OF CONTROL OF THE MOTORCYCLE WHICH COULD RESULT IN SERIOUS INJURY OR DEATH.

NOTICE Ensure the gas cap is properly tightened BEFORE riding.

Kuryakyn will not provide warranty coverage or be liable for incidental or consequential damages resulting from the use of incorrect gaskets.



INSTALLATION INSTRUCTIONS

MESH GAS CAP, VENTED, SATIN BLACK

6549

-CONTINUED-

