

INSTALLATION INSTRUCTIONS

DILLINGER HANDGUARDS, SILVER

6708

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Left Handguard (clutch side)
- 1 Right Handguard (brake side)
- 2 5/16 External Tooth Lock Washer

YOU WILL ALSO NEED:

Torx wrench set, combination wrench set, hex wrench set, flat head screw driver

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.



STEP 2 Refer to PIC 2. Remove existing mirror and mirror mounting hardware from handlebar perch. Set all side, they will be reused.



STEP 3 Refer to PIC 3. Locate provided Left Handguard and one (1) External Tooth Lock Washer. Align the washer on top of the mounting hole of the handguard bracket.



INSTALLATION INSTRUCTIONS

DILLINGER HANDGUARDS, SILVER

6708

-CONTINUED-

STEP 4 Refer to PIC 4. Locate the mirror and hardware that was removed in Step 2. Fasten the handguard to the handlebars using the mirror and mirror mounting hardware.

STEP 5 Repeat Steps 2 through 5 on the Right (brake) side.



PIC 4

NOTICE IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



FINAL