

INSTALLATION INSTRUCTIONS

LUGGAGE RACK FOR GL1800, GLOSS BLACK

7157

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- | | | | |
|---|-----------------------------------|---|---|
| 1 | Luggage Rack with Rubber Insert | 1 | Hardware Kit, containing: - CONTINUED - |
| | Hardware Kit, containing: | 2 | #10-24 x 1" Button Head Cap Screws |
| 4 | Cup washers | 2 | #10-24 x 1-1/4" Button Head Cap Screws |
| 2 | Rubber Spacers with Adhesive Back | 4 | 1/4" Flat Washer |
| 8 | Rubber washers | | |

YOU WILL ALSO NEED:

Set of Hex Wrenches, Drill and Drill Bits, Masking Tape, and a Marker or Pen

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

STEP 2 Without letting the Luggage Rack contact the Trunk Lid, hold it in the approximate mounting location. Place masking tape on the top (painted) surface of the trunk lid in the location of the luggage rack legs to prevent scratching.

CAUTION MEASURE TWICE - DRILL ONCE. DOUBLE CHECK ALL REFERENCE MARKS MADE ON THE TRUNK LID BEFORE DRILLING. KURYAKYN WILL NOT BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THIS INSTALLATION.

STEP 3 Align and place the luggage rack on top of the tour box, with the legs resting on top of the taped areas. Trace the location of the legs on the tape. Carefully mark the center of your tracings.

STEP 4 Double check to be certain the rack is centered in the position you desire.

STEP 5 FOR '01-'17 MODELS ONLY
On the inside of the tour box, remove the hardware and inner surface from the top lid.

FOR '18+ MODELS
Continue to Step 6.



INSTALLATION INSTRUCTIONS

LUGGAGE RACK FOR GL1800, GLOSS BLACK

7157

-CONTINUED-

STEP 6 On the outside of the trunk lid, carefully drill a 1/4" hole at the center of the marked locations. Remove masking tape from around the mounting holes.

Tip: You may want to drill a smaller diameter pilot hole first. This will lessen the chance of the drill "walking" and harming the finish. While drilling the rear holes, try to match the angle of the rear mounting legs.

STEP 7 Locate provided two (2) cup washers, four (4) rubber washers, (2) flat washers, and two (2) 10-24 x 1" Button Head Cap Screws. Place a flat washer followed by a rubber washer onto each of the screws.

STEP 8 Refer to PIC 2 and 3. From the inside of the lid insert the screw washer assembly through the front mounting hole. On the outside of the lid, place a rubber washer followed by the cupped washer onto the protruding screw. Align the rack's front foot with the hardware and fasten it to the lid. Fully tighten hardware, but do not overtighten.

STEP 9 **FOR '01-'17 MODELS ONLY**
Locate provided two (2) rubber spacers with adhesive backing. Remove the backing from the spacers. From the inside of the trunk lid, align and place the spacers over the **REAR** drilled mounting holes. Reinstall the inner surface of the trunk lid in the reverse order of which it was removed in Step 5.

FOR '18+ MODELS
Proceed to Step 10.

STEP 10 Locate provided two (2) cup washers, four (4) rubber washers, (2) flat washers, and two (2) 10-24 x 1-1/4" Button Head Cap Screws. Place a flat washer followed by a rubber washer onto each of the screws.

STEP 11 From the inside of the lid insert the screw washer assembly through the rear mounting hole. On the outside of the lid, place a rubber washer followed by the cupped washer onto the protruding screw. Align the rack's rear foot with the hardware and fasten it to the lid. Fully tighten hardware, but do not overtighten.

CAUTION

NEVER EXCEED THE MANUFACTURER'S RECOMMENDED LOAD CAPACITY. EXCESS LOADING ON THE LUGGAGE RACK COULD CAUSE DAMAGE TO YOUR MOTORCYCLE, LOSS OR INJURY. KURYAKYN IS NOT RESPONSIBLE FOR ANY DAMAGE, LOSS, OR INJURY CAUSED BY EXCEEDING THE MANUFACTURER'S LOAD CAPACITY.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



PIC 2



PIC 3