



SADDLE SHIELD HEAT DEFLECTORS FOR INDIAN

7181

Thank You For Choosing Küryakyn!

Protect yourself and others from potential injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

NOTICE

This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality or damage the product itself or the product to which it is being attached.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Right Saddle Shield
- 1 Left Saddle Shield
- 1 Alcohol Pad
- 1 Protective Film
- 1 Installation Instructions

YOU WILL ALSO NEED:

Set of metric hex wrenches, metric hex bit sockets, ft lbs (Nm) torque wrench

NOTICE

These installation instructions contain important information. Ensure that the end user receives this copy and is aware of its importance for future use.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn **IGN OFF**. Allow the engine and exhaust system to cool.

WARNING

INSTALLATION MAY REQUIRE CONTACT WITH THE ENGINE AND EXHAUST SYSTEM; ENSURE THAT IT HAS FULLY COOLED BEFORE BEGINNING TO PREVENT INJURY.

NOTICE

Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2 Remove both side covers and the seat; set the covers, seat, and screws aside for now.

STEP 3 Refer to **PIC 1**. Remove the rear tank screws; set them aside, they will be reused.

STEP 4 Locate the Right and Left Saddle Shields.

STEP 5 Refer to **PIC 2**. Apply the included Protective Film to the underside of the fuel tank.

STEP 6 Refer to **PIC 2**. Align the holes and secure the Saddle Shields with the existing screws and washers; **torque to 12 ft lbs (16.3)**.

STEP 7 Repeat for the other side.





STEP 8 Reinstall the seat and side covers.

Pull upward on the front of the seat to ensure that it is properly installed before operating the motorcycle.

Clean the saddle shields with warm, soapy water and a clean cloth.

Some cleaning products contain chemicals that can severely damage product.

Only use cleaning products formulated for polycarbonate plastic.

NOTICE

It is the end user's responsibility to ensure that all fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not provide warranty coverage on products or components lost or damaged due to improper installation or lack of maintenance. Periodic inspection and maintenance are required on all fasteners.