



## KURYAKYN FOOTPEG ADAPTERS for GL 1800

7939

### PARTS INCLUDED

- 1 Peg Adapter Set
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

### TOOLS SUGGESTED

Needle Nose Pliers

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.
- STEP 2** Remove the stock pegs from the OEM mounts by removing the cotter pin and washer from the bottom of the mounting pin. Watch how the placement of the spring is connected to the peg and the hole in the mount. Keep all these parts, they will be reused.
- STEP 3** Reconnect the new peg adapter to the mount while making sure that the spring is in the proper position. Drop mounting pin back into position and secure with washer and cotter pin. Check to make sure that your peg adapter pivots up freely.
- STEP 4** Position the peg on the peg adapter and tighten the 5/16"-18 socket head cap screw located on the end of the peg. The peg adapter will seat itself into the peg and keep it from rotating.
- STEP 5** Repeat above steps for other side.

**WARNING!** THE INSTALLATION OF AFTERMARKET PEGS MAY AFFECT GROUND CLEARANCE WHEN CORNERING.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*