



**REAR MASTER CYLINDER COVER 8653**

**FOR '08 H-D / BREMBO**

**FITS: '08-UP ELECTRIC GLIDES, ROAD KINGS, ROAD GLIDES, AND STREET GLIDES**

**PARTS INCLUDED**

- 1 Rear Master Cylinder Cover
- 1 Hardware Kit, Including:
  - 2 M4-0.7 x 20 Socket Button Head Cap Screws
  - 2 3.5 Narrow Washers
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

**THANK YOU FOR CHOOSING KÜRYAKYN!**

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**TOOLS SUGGESTED**

Set of hex wrenches, Phillips screwdriver.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**PROCEDURE**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

**STEP 2** Remove the two Phillips screws located on the top of the rear master cylinder reservoir cover. They will not be reused. See PIC. 1.

**NOTE:** *This is a good time to check and top off the rear brake reservoir. DOT 5 for non ABS models and DOT 4 for models with ABS.*

**STEP 3** Take the two provided M4-0.7 x 20 Socket Button Head Cap Screws; and the two 3.5 Narrow Washers and insert them in each location on the top of the chrome master cylinder cover.

**STEP 4** With the stock brake reservoir cover in hand, place it on the inside of the chrome master cylinder cover and on the two cap screws that were installed in STEP 3.

PIC. 1



**-cont.-**

**STEP 5** Carefully place the covers over the master cylinder reservoir and start the two cap screws.

**STEP 6** Tighten both cap screws evenly.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*

**Küryakyn**<sup>®</sup>

PIC. 2

