



**PLUG AND PLAY SISSY BAR MOUNT**

**8998**

**PARTS INCLUDED**

- 1 Plug and Play Sissy Bar Mount
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

**THANK YOU FOR CHOOSING KÜRYAKYN!**

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

**TOOLS SUGGESTED**

Set of Hex Wrenches, Combination Wrenches, Socket Set and Ratchet, Drill Bits, Drill, Masking Tape.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

**ATTENTION!** This procedure may require making permanent modifications to the fender; this may void your warranty. Consult your dealer for more information.

**NOTE:** This product is recommended for use on steel fenders only.

**NOTE:** Accepts aftermarket or OEM H-D sissy bar uprights that are NO MORE THAN 10" TALL, 6-11/16" wide- this sissy bar is commonly used on FXR's, '91-'01 Dynas, and '03-earlier Sportsters

**STEP 2** Remove the seat from the motorcycle and clean the fender.

**STEP 3** Place the mount on the fender and determine a mounting location; you may choose to slightly bend the backbone to conform to the contour of the fender for a better fit.

**-cont.-**

**STEP 4** Once a location has been determined, fit the seat to make sure the location of the bracket will work with the seat.

**NOTE:** Generally the rear mounting hole in the mounting plate will be placed so that it will be secured with the rear seat mounting bolt, though it may be positioned in any location by drilling two holes.

**STEP 5** Once mounting location has been determined, place masking tape on the fender in the location where the hole(s) will be drilled and mark the hole location.

**STEP 6** Carefully drill a hole(s) in the marked location(s), using the appropriate sized drill bit for the hardware that you chose to secure the mount; be careful not to drill into the tire.

**CAUTION!** **MEASURE TWICE – DRILL ONCE.** Double check all reference marks made on the rear fender **BEFORE** drilling. Kuryakyn will not be responsible for incidental or consequential damages resulting from this installation.

**CAUTION!** Ensure that the area below the fender is clear before drilling. Be careful not to drill into the tire or any concealed wiring!

**CAUTION!** To minimize the possibility of damage to the paint we recommend the use of masking tape and a sharp drill bit.

**STEP 7** Carefully remove the tape from the fender.

**STEP 8** Thoroughly clean the fender to remove any metal shavings and/or dust, dirt or grime to prevent damage to the paint.

**STEP 9** Place the mount on the on the fender and secure using your hardware, ensuring that any hardware will not be too long and interfere with the tire at any point during operation of the motorcycle.

**NOTE:** If using existing holes make sure to use the proper thread pattern, washer and bolt size specific to your fender.

**CAUTION!** Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

**STEP 10** Install a sissy bar that is no more than ten (10) inches (not included) and secure to the bracket.

**WARNING!** DO NOT EXCEED 10" HEIGHT RESTRICTION-USE OF TALLER SISSY BARS MAY RESULT IN FENDER DAMAGE, SERIOUS INJURY OR DEATH.

**STEP 11** Tighten all hardware securely.

**WARNING!** SISSY BARS ARE NOT A SAFETY RESTRAINING DEVICE. FAILURE TO HOLD ONTO THE MOTORCYCLE MAY RESULT IN INJURY OR DEATH.

**WARNING!** IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*