

INSTALLATION INSTRUCTIONS

SEAT RELEASE

9035

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Rear Seat Mount Cap
- 1 1/4" Nylon Spacer Washer
- 1 1/4-20 x 1/2 Knurled Knob
- 1 1/4-28 x 1/2 Knurled Knob

YOU WILL ALSO NEED:

Phillips Head Screwdriver, Set of Combination Wrenches

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2** Remove the seat from the motorcycle.
- STEP 3** Loosen the two 1/4" bolts that hold the mounting tab to the seat.
- STEP 4** Slide the chrome seat tab cap into position over the stock seat tab. Be certain the holes in the cover line up with the holes in the tab.
- STEP 5** Tighten the two seat tab mounting screws.
- STEP 6** Reposition the seat on the motorcycle.
- STEP 7** Place the plastic spacer washer between the tab and the fender to prevent fender damage.
- STEP 8** Match the threads of the two knurled knobs to the threads of the stock seat screw removed earlier, and secure the seat with the appropriate nob. Tighten securely.

NOTICE IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.