

# Product information

## Hydraulic Lifter Additive

PI 17/29/06/2017



### Description

High performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning again.

### Properties

- damps hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil
- tested for turbochargers and catalytic converters

### Technical data

Color / appearance	hellbraun / light brown
Appearance / properties	viskose Flüssigkeit / viscous liquid
Density at 20 °C	0,887 g/cm <sup>3</sup> DIN 51757
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 20 °C	1100 mPas

### Areas of application

For all gasoline and diesel engines. Can be mixed with all commercially available motor oils

### Application

One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 1.6 gal (6 liters) motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change. Minimum oil filling of 3 liters (3.17 U.S. QT) is requested for optimum product performance.

### Comment

**Not suitable for use on motorbikes with wet clutches.**



### Available pack sizes

300 ml Can sheet metal	1009 D-F-NL
300 ml Can sheet metal	2770 GB-GR-I
300 ml Can sheet metal	8345 D-PL-BG
300 ml Can sheet metal	8354 D-E-P
300 ml Can sheet metal	8367 GB-ARAB-F
300 ml Can sheet metal	8382 D-H-RO
300 ml Can sheet metal	8338 DK/N-S-FIN
300 ml Can sheet metal	2783 GB-AUS
300 ml Can sheet metal	20004 GB-F-E-USA-CAN
300 ml Can sheet metal	3919 D-RUS-UA
300 ml Can sheet metal	20801 SLO-SRB-HR
205 l Drum sheet metal	2581 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**