

Product information

LM 48 Installation Paste

PI 17/31/08/2017



Description

High-performance tungsten disulfide paste for heavy-duty applications. It adheres even to apparently smooth surfaces. Rubbed into bearings and slide-ways, it prevents running-in damage and seizing marks when assembling components with tight pairings. Contains a synergistically active solid lubricant system with a zinc sulfide, graphite, fluorides and tungsten disulfide base. Operating temperature range: -35 °C to +450 °C.

Properties

- outstandingly adherent
- high capacity
- high wear resistance
- good corrosion protection
- low coefficient of friction
- easy to use
- outstanding emergency-running properties
- highly economical

Technical data

Color / appearance	schwarz / black
Base	Mineralöl / mineral oil
Density at 20 °C	1 g/ml
Pressfit test (no stick slip)	0,12 µ
Thread friction	0,09 µ
Operating temperature range	-35 bis +450 / -35 to +450 °C
Form	pastös, flüssig / pastelike, liquid
Odor	geruchslos / odourless
Viscosity at 40 °C	<7 mm ² /s
Flash point	101 °C

Areas of application

For assembly, repair, and maintenance in all areas of engineering. For basic lubrication and to prevent running-in damage and seizure marks when press-fitting bolts and bushings as well as installing roller bearing rings. For lifetime lubrication of joints and small components and for reducing wear on sliding machine components.

Application

Apply to cleaned surfaces using a paint brush, brush or lint-free cloth. Do not rub in. Can be applied in excess.

Available pack sizes

50 g Tube plastic	3010 D
1 kg Can sheet metal	4096 D-GB-I-NL-F

Our information is based on thorough research and may be considered reliable, although not legally binding.