

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 0W-40 MOTORCYCLE OIL

PRODUCT # 10718, 10756, 10758

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>35.4</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8478</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.059</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>70</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>14</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>210</b>
<b>Color</b>		<b>Light Brown</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>370</b>

**Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation. This particular formulation is a high performance blend designed for easy cold weather starting. Especially recommended for snow mobile, 4-stroke engines.**

**Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.**

**The exclusive additive package in Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil allows for extended drain intervals.**

**Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil far exceeds all OEM specifications.**

**Formulated to meet ALL motorcycles that call for a Synthetic SAE 0W-40 motor oil.**

**Meets or exceeds: API SM, SL, SJ, SH, SG, SF, CC, CD • JASO MA/MA-2 • ACEA A3**