Technical Data Sheet



TUNDRA SNOWMOBILE

HIGH PERFORMANCE 2-STROKE ENGINE OIL

DESCRIPTION:

<u>Mineral based 2-stroke engine oil designed to ensure optimum protection</u> and performance for snowmobiles. Clean burning, low-smoke formulation utilizes high quality base stocks and anti-wear additives to protect critical engine parts at even the most extreme low temperatures. Advanced, low-ash additive system minimizes carbon build up while preventing rust, corrosion and wear. Exceeds JASO FD / ISO-L-EGD / API TC specifications.

FEATURES & BENEFITS:

- Optimum hardware protection for all critical engine parts
- Protects at even the most extreme low temperatures
- Clean burning, low-smoke formulation ensures engine cleanliness
- Advanced, low-ash additive system prevents ring stick, corrosion and wear
- Exceeds JASO FD / ISO-L-EGD / API TC specifications

APPLICATIONS:

For all 2-stroke gasoline snowmobile engines. Can be used as premix or in oil injection system. Safe for use at any OEM-recommended ratio.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	RESULT
APPEARANCE	VISUAL	Brown
VISCOSITY @ 40°C (cSt)	D445	36.5
VISCOSITY @ 100°C (cSt)	D445	6.4
FLASH POINT (°C)	D92	172
POUR POINT (°C)	D97	-45
DENSITY @ 15 °C (g/ml)	D4052	0.860

EXPERIENCE THE DIFFERENCE