

V-TWIN MINERAL

HIGH PERFORMANCE 4-STROKE ENGINE OIL

DESCRIPTION:

Mineral based 4-stroke engine oil specifically formulated for V-Twin engines. Shear-stable formulation provides excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system with industry leading extreme pressure and anti-wear protection keeps your engine running clean, trouble-free and extends the life of the machine. Exceeds the requirements of API SL / JASO MA2.

FEATURES & BENEFITS:

- Formulated specifically for V-Twin engines
- Superior protection at any temperature
- Excellent clutch feel and clutch protection
- Shear stable formula maintains oil viscosity and film thickness
- Optimizes cleanliness while controlling oxidation and wear
- Exceeds API SL and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled V-Twin 4-stroke gasoline engines.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	10W-40	20W-50	25W-60	50WT	60WT	70 WT
APPEARANCE	VISUAL	Amber	Amber	Amber	Amber	Amber	Amber
VISCOSITY @ 40°C (cSt)	D445	95.4	167.7	259.3	-	-	-
VISCOSITY @ 100°C (cSt)	D445	14.8	20.3	24.6	-	-	-
VISCOSITY INDEX	D2270	162	141	120	-	-	-
FLASH POINT (°C)	D92	206	208	-	-	-	-
POUR POINT (°C)	D97	-36	-30	-	-	-	-
DENSITY @ 15 °C (g/ml)	D4052	0.866	0.871	-	-	-	-