



# SXS SYNTHETIC ENGINE

## 100% SYNTHETIC, ESTER-FORTIFIED 4-STROKE ENGINE OIL

### DESCRIPTION:

Full synthetic, ester-fortified 4-stroke engine oil specifically formulated for side-by-side (SXS) engines. Synthetic, oxidatively-stable formulation combines surface-active esters with a shear-stable polymer system to provide excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system reduces temperatures and increases power output while keeping your engine running clean, trouble-free and extending the life of the machine. Exceeds the requirements of API SL / JASO MA2.

### FEATURES & BENEFITS:

- Recommended for all OEM equipment
- Formulated specifically for SXS engines
- Superior protection and oxidative stability at any temperature
- Reduces temperature and increases power output
- Shear-stable, ester-fortified formula maintains oil viscosity and film thickness
- Surface-active chemistry aggressively attaches to engine surfaces and keeps them clean
- Exceeds API SL and JASO MA2 specifications

### APPLICATIONS:

For all air and water-cooled SXS 4-stroke gasoline engines.

### TECHNICAL DATA

| SPECIFICATION           | TEST METHOD | 0W-40 | 5W-50 | 10W-50 |
|-------------------------|-------------|-------|-------|--------|
| APPEARANCE              | VISUAL      | Amber | Amber | Amber  |
| VISCOSITY @ 40°C (cSt)  | D445        | 84.3  | 106.5 | 138.3  |
| VISCOSITY @ 100°C (cSt) | D445        | 14.6  | 18.2  | 19.6   |
| VISCOSITY INDEX         | D2270       | 181   | 191   | 162    |
| FLASH POINT (°C)        | D92         | -     | 230   | 225    |
| POUR POINT (°C)         | D97         | -     | -48   | -45    |
| DENSITY @ 15 °C (g/ml)  | D4052       | 0.864 | 0.856 | 0.858  |