

SCOOTER GEAR OIL

HIGH PERFORMANCE GEAR OIL

DESCRIPTION:

<u>Mineral-based gear oil specifically formulated for use in 2-stroke or 4-stroke scooters and mopeds</u>. Robust, shear-stable formulation maintains oil film thickness to protect transmissions under severe stop-and-go city driving conditions. Proprietary shape combines the finest mineral base stocks with industry leading extreme pressure and anti-wear additives to ensure hardware protection and smooth shifting during full throttle accelerations. Exceeds the requirements of API GL-4 and GL-5.

FEATURES & BENEFITS:

- Formulated specifically for use in 2-stroke or 4-stroke scooters and mopeds
- Superior protection from wear, pitting and spalling
- Shear stable formula is robust enough for stop-and-go city driving conditions
- Robust formulation ensures protection under high loads and full throttle accelerations
- Exceeds API GL-4 and GL-5 specifications

APPLICATIONS:

For all 2-stroke or 4-stroke scooters and mopeds where a 90wt gear oil or 30wt engine oil is recommended. Can be used in hypoid/shaft drive gears. Not for use in transmissions with wet-clutches.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	80W-90
APPEARANCE	VISUAL	Green
VISCOSITY @ 40°C (cSt)	D445	171.7
VISCOSITY @ 100°C (cSt)	D445	16.3
VISCOSITY INDEX	D2270	99
FLASH POINT (°C)	D92	397
POUR POINT (°C)	D97	-27
DENSITY @ 15 °C (g/ml)	D4052	-