

Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier: Product Name: Synthetic Chain Guard Crystal Clear

Maxima Racing Oils Article Number: 77920

Generic Chemical Name: Synthetic Oil - Aerosol

Applications: Chain Lubricant

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable Aerosol Category 1
Gas Under Pressure Liquefied Gas
Aspiration Toxicity Category 1
Skin Irritation Category 2
Reproductive Toxicity Specific Target Organ
Toxicity Repeat Exposure
Category 2
Category 2

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Label Elements:

GHS Pictogram









Signal Word DANGER!

Hazard Statements Extremely Flammable Aerosol.

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to nervous system through prolonged or repeated

exposure

Precautionary Statements

Prevention Obtain special instructions before use.



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces – No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe vapors or mists.

Wash thoroughly with soap and water after handling.

Wear protective gloves

Response IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT

induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF exposed or concerned: Get medical advice.

Storage Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store in a well-ventilated place

Disposal Dispose of contents and container in accordance with local and national

regulations.

Other Hazards None

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Components | Content % | CAS Number | US Hazcom 2012/ GHS Classification |
|---|----------------|--------------------------|------------------------------------|
| Distillates, hydrotreated heavy paraffinic Liquefied Petroleum Gas (Propane, Isobutane) | 20-30 20-30 | 64742-54-7 68476-86-8 | Not Hazardous |
| Equencu i etroleum dus (i ropune, isosutune) | 20 30 | 00470 00 0 | Flammable Gas |
| | | | Category 1 Gas Under Pressure, |
| | | | Liquefied Gas |
| n-Hexane | 10-20 | 110-54-3 | Flammable Liquid |
| | | | Category 2 |
| | | | Aspiration Toxicity |
| | | | Category 1 |
| | | | Skin Irritation |
| | | | Category 2 |
| | | | Reproductive Toxicity |
| | | | Category 2 |
| | | | Specific Target Organ |
| | | | Toxicity Single |
| | | | Exposure Category 3 |
| | | | (nervous system |
| | | | effects) |



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

Specific Target Organ Toxicity Repeat Exposure Category 2

Note: The specific identity and/or exact percentage been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation If irritation is experienced, move to fresh air. Get medical attention if irritation

or other symptoms develop and persist.

Skin Contact Wash with soap and water for several minutes. Remove contaminated

clothing and wash before reuse. If irritation develops and persists, get medical

attention.

Eye Contact Flush thoroughly with water. Remove contact lenses if present after the first 5

Immediate medical attention is needed for ingestion.

minutes and continue flushing for 15 minutes. Get medical attention if

irritation persists.

Ingestion Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control

center.

Most Important

Symptoms

May cause skin irritation. Inhalation may cause drowsiness, dizziness and other nervous system effects. Harmful or fatal if swallowed. Aspiration of liquid into the lungs during swallowing or vomiting may cause lung damage. N-Hexane exposure can cause peripheral neuropathies. Initial symptoms include numbness in the extremities. Motor weakness may also occur. Prolonged exposure may cause reproductive harm and may damage the

nervous system.

Indication of Immediate Medical

Attention Needed

Notes to Physician Treat appropriately.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing

Media

Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and

spread fire.

Specific Hazards
Arising From The
Chemical

Extremely flammable aerosol. Highly flammable liquid and vapor. Contents under pressure. Keep away from ignition source and open fire. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion baserd in confined spaces.

and air mixture can create an explosion hazard in confined spaces. Combustion will produce oxides of carbon, saturated and unsaturated

hydrocarbons.



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

Special Protective Equipment And Precautions For FireFirefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with

water. Use shielding to protect against bursting containers.

Fighters

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Wear appropriate protective clothing (see Section 8). Eliminate all sources of

ignition and ventilate area

Environmental Hazards

Methods/Materials for

Cleaning up

Leaking cans should be placed in a plastic bag or open pail until the pressure

has dissipated. Contain and collect liquid with an inert absorbent and place in

a container for disposal. Clean spill area thoroughly. Report spills to

authorities as required.

Not determined

7. HANDLING AND STORAGE

Precautions for Safe

Handling:

Avoid contact with eyes and skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights,

hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of

electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

Conditions for Safe

Storage

Store in a cool, well-ventilated area, away from incompatible materials. Do

not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3

Aerosol. Store away from oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits Distillates, hydrotreated heavy 5 mg/m3 TWA ACGIH TLV

paraffinic (inhalable) (as mineral Oil)

5 mg/m2 TWA OSHA PEL (as oil

mist, mineral)

Propane 1000 ppm TWA OSHA PEL Isobutane 1000 ppm STEL ACGIH TLV n-Hexane 50 ppm TWA ACGIH TLV (skin)

500 ppm TWA OSHA PEL



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

The Following Controls are Recommended for Normal Consumer Use of this Product

Appropriate Use in a well-ventilated area.

Engineering Controls Personal Protection

Respiratory None needed for normal use with adequate ventilation

Protection:

Eye Protection: Avoid eye contact. Always spray away from your face

Skin/Body Protection: Avoid prolonged skin contact. Chemical resistant gloves recommended for

operations where skin contact is likely

For Bulk Processing or Workplace Use the Following Controls are Recommended

Appropriate Use adequate general and local exhaust ventilation to maintain exposure

Engineering Controls levels below that occupational exposure limits

Personal Protection

Respiratory None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow

OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice

Eye Protection: Safety goggles recommended where eye contact is possible

Skin/Body Protection: Wear chemical resistant gloves

Work/Hygiene Wash with soap and water after handling

Practices:

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid

ColorColorless to pale yellowOdorMild hydrocarbon odor

Odor Threshold Not established PH Not applicable Freezing Point Not established

Boiling Point 145.4-156.2°F (63-69°C) (n-Hexane)

Flash Point -14.8°F (-26°C) (n-Hexane)

Evaporation Rate Not established **Flammability (solid, gas)** Flammable Aerosol

Upper Explosion Limit 7.7% Lower Explosion Limit 1.2%

Vapor Pressure 153 mmHg @ 77°F (25°C) (n-Hexane)

Vapor Density (Air=1) Not established
Relative Density Not established
Solubility Insoluble in water
Partition Coefficient: nNot established



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

octanol/water

Auto Ignition Not established

Temperature

Decomposition Not established

Temperature

Volatile Organic 37%

Compounds (VOC)

Viscosity Not established **Pour Point** Not established

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

Chemical Stability Stable.

Possibility of Hazardous None known.

Reactions

Conditions to Avoid Avoid heat, sparks, flames and other sources of ignition. Do not puncture or

incinerate containers.

Incompatible Materials Strong oxidizers.

Hazardous Decomposition Product Thermal decomposition will generate oxides of carbon, saturated

and unsaturated hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Potential Health Hazards

Eye Contact: Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing **Skin Contact:** May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis.

Inhalation: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. The liquid contents are an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis

Chronic Effects: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA

Reproductive Toxicity: Prolonged exposure to n-hexane has resulted in decreased sperm count and degenerative changes in the testes of rats but not mice

Numerical Measures of Toxicity: Distillates, hydrotreated heavy paraffinic: Oral rat LD50: >5000

mg/kg, Dermal rabbit LD50: >5000 mg/kg

Liquefied Petroleum Gas: No toxicity data is available

n-Hexane: Oral rat LD50: 16,000 mg/kg, Inhalation rat LC50: >31.86 mg/L/4hr, Dermal rabbit LD50:



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

>2,000 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

n-Hexane: 96 hr LC50 Fathead minnow- 2.5 mg/L, 48 hr EC50 Daphna magna-

2.1 mg/L, 72 hr EbL50 Green algae- 26 mg/L

This product is expected to be harmful to the aquatic environment with long-term adverse effects. Releases to the environment should be avoided.

Biodegradation n-Hexane: Readily biodegradable-83% in 28 days.

Bioaccumulation There is a potential for bioaccumulation.

Mobility in soil No data available.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Disposal If this product becomes a waste, it would be expected to meet the criteria

of a RCRA ignitable hazardous waste (D001). However, it is the responsibility

of the generator to determine at the time of disposal the proper classification and method of disposal. Do not puncture or incinerate

containers, even empty. Dispose in accordance with federal, state, and local

regulations.

14. TRANSPORT INFORMATION

| | UN Number | Proper shipping name | Hazard Class | Packing Group | Environmental Hazard |
|------|-----------|----------------------|-----------------|------------------|-------------------------|
| DOT | 1950 | Aerosols | 2.1 | | |
| IMDG | 1950 | Aerosols | 2.1 | LTD QTY | |
| ICAO | 1950 | Aerosols, flammable | 2.1 | | |
| | | | | | |

Special precautions: None known.

15. REGULATORY INFORMATION

CERCLA: Releases of this product in excess of the reportable quantity of 25,000 pounds based on the Rt for n-Hexane of 5,000 lbs present at less than 20% must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.



Version: 1.1

Released: 2015-06-01 Revision Date: 2015-05-28

EPA SARA 311/312 Hazard Classification: Acute Health, Chronic Health, Fire Hazard, Sudden Release of Pressure

EPA SARA 313: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: n-Hexane 110-54-3 10-20%

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules

California Proposition 65: This product does not contain chemicals regulated under California Proposition 65.

Canadian CEPA: All of the components are listed on the Canadian Domestic Substances List or exempt from notification

16. OTHER INFORMATION

NFPA Rating (NFPA 704): Health: 2 Fire: 3 Instability: 0 HMIS Rating: Health: 2 Fire: 3 Physical Hazard: 0

Date of Revision: May 28, 2015

Date of Previous Revision: August 2004

Revision History:

5/28/15: Converted to GHS format. All section revised

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.