



DOT 4 BRAKE FLUID

UNIVERSAL BRAKE & CLUTCH FLUID

DESCRIPTION:

High performance brake and clutch fluid designed to lubricate and protect critical brake system componentry while providing reliable stopping power. Anti-vapor lock formulation maintains responsiveness and performance by fighting both water contamination and vaporization. Advanced chemistry resists corrosion, oxidation and is compatible with SBR, EPDM and natural rubbers. Exceeds the requirements of US FMVSS 116 DOT 3 & DOT 4, SAE J1703, SAE J1704 and ISO 4925 (Classes 3 & 4).

FEATURES & BENEFITS:

- For use in all vehicles specifying DOT 3 or DOT 4 brake fluid
- Durable and reliable stopping power
- Anti-vapor lock formulation maintains responsive lever and pedal feel
- Resists corrosion, oxidation and “boil-off”
- Mixes with other DOT 3 and DOT 4 brake fluids
- Exceeds US FMVSS 116 DOT 3 & DOT 4, SAE J1703, SAE J1704 and ISO 4925 (Classes 3 & 4)

APPLICATIONS:

For use in all hydraulic clutch systems and all brake systems specifying DOT 3 and DOT 4 brake fluids. Do not use in DOT 5 silicone brake systems or mix with silicone based fluids.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	RESULTS
APPEARANCE	VISUAL	Amber
DRY BOILING POINT (°C/°F)	FMVSS 116	243/469
WET BOILING POINT (°C/°F)	FMVSS 116	159/318
VISCOSITY @ -40°C (cSt)	D445	1300