Motion Pro Multi Purpose Adhesive and Grip Glue MSDS



MATERIAL SAFETY DATA SHEET

Grip Glue

15-0003

07/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Grip Glue 15-0003

Product Type: Adhesive

Company: Motion Pro, Inc.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state:
 Liquid
 HEALTH:
 3*

 Color:
 Clear
 FLAMMABILITY:
 0

 Odor:
 Ether-like
 PHYSICAL HAZARD:
 0

Personal Protection: See Section 8

WARNING: MAY CAUSE EYE, AND SKIN IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

Primary Routes of Entry: Skin, Inhalation, Eyes

Signs and Symptoms of Exposure:

Inhalation: Dizziness may occur at 200 ppm; Progressively higher levels can cause

irritation of the respiratory tract, drunkenness, nausea, uncoordination, unconsciousness and even asphyxiation in confined areas. Overexposure can

cause central nervous system damage.

Skin contact: Irritation can develop following repeated and/or prolonged contact and may

cause drying or flaking of skin. A single prolonged exposure is not likely to result in material being absorbed through the skin in harmful amounts. The LD50 of Tetrachlorothylene for skin absorption in rabbits is >10,000 mg/kg.

Eye contact: Product in eyes can result in discomfort, pain and irritation. Vapors may

irritate the eyes at about 100 ppm.

Ingestion: Single dose oral toxicity is low. Ingestion may result in irritation of the mouth

and gastrointestinal tract along with other effects as listed for inhalation. Vomiting and subsequent aspiration into the lungs may lead to injury of other

body systems

Existing Conditions Aggravated by Exposure: Increased rate of spontaneously occurring malignant tumors in certain lab rats

and mice. Prolonged exposure above OSHA permissible limits may result in

None

liver and kidney damage. Pre-existing eye, skin, and lung conditions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients <u>%</u> ACGIH TLV OSHA PEL OTHER

 Tetrachloroethylene
 70-100
 170 mg/m³ TWA
 100 ppm TWA

 685 mg/m³ TWA
 200 ppm Ceiling

STEL



MATERIAL SAFETY DATA SHEET

Grip Glue 15-0003

07/2014

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Call physician. Give 1 or 2 glasses of water to drink.

Inhalation: Remove to fresh air. If breathing difficulty, give oxygen. Give artificial

resuscitation if not breathing.

Skin Contact: Wipe from skin and wash with soap and water. If irritation develops, seek

medical attention.

Eye Contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash Point (TCC): None

Recommended Extinguishing Agents: Carbon dioxide, foam, dry chemical, water fog

Special Firefighting Procedures: None

Hazardous Combustion Products: Not available

Unusual Fire or Explosion Hazards: Cool fire exposed containers with water. If storage containers are exposed to

excessive heat, over-pressurization can result in container rupture. Product is non-flammable and non-explosive under normal conditions of use. At high temperatures, product decomposed to give off hydrochloric acid as gas plus

other toxic and irritating vapors such as phosgene and chlorine.

Flammable/Explosive Limits – lower %: Not available
Flammable/Explosive Limits – upper %: Not available

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear proper protective equipment

Measures for Environmental Protection: Do not allow entry into drains or surface waters

Clean-up Measures: Small leaks: Wipe up, or soak up immediately with inert material. Remove to

outdoors. Large spills: Evacuate area; contain liquid; transfer to closed metal

containers; keep out of water supply.

7. HANDLING AND STORAGE

Handling: Do not enter confined spaces unless special breathing apparatus is used and

an observer is present.

Storage: Store between 46° and 82°F unless otherwise labeled to preserve shelf life. In

large quantities, lethal concentrations may exist in areas with poor ventilation. Do not use in poorly ventilated or confined spaces without proper respiratory protection. Vapors will collect in low places such as pits, storage tanks and

other confined spaces.



Grip Glue

15-0003

07/2014

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye/Face Protection: Safety glasses or goggles with side shields

Skin Protection: Use rubber or plastic gloves, and protective clothing as necessary

Respiratory Protection: Use NIOSH approved respirator if there is a potential to exceed exposure

limits

Engineering Controls: Adequate ventilation should be provided to keep vapor concentration below

acceptable exposure guidelines. Use only with adequate ventilation. Avoid breathing vapors. If ventilat6ion is inadequate to maintain atmospheric levels below the TLV, wear a NIOSH approved air purifying organic cartridge respirator. For emergency and overexposure, use an approved positive pressure self-contained breathing apparatus. In confined or poorly ventilated

areas, use an approved pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Color: Clear
Odor: Ether-like

Vapor Pressure: 13 mm Hg at 68°C

Vapor Density: Heavier than air Solubility in Water: Negligible

Specific Gravity: 1.38

Boiling Point: > 250°F

Volatile Organic Compound Content 0.01 |b/g|

Evaporation Rate (Ether = 1) Slower than ether

pH: Does not apply

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Toxic / irritating gases and fumes. Hydrogen chloride, CO2, simple

hydrocarbons, phosgene and chlorine.

Incompatibility: Strong acids and oxidizing materials. Avoid mixing with caustic soda or

potash.

11. TOXICOLOGICAL INFORMATION

Literature Referenced Target Organ

ature Referenced Target Organ Carcinogen Status

Ingredients: and Other Health Effects

NTP IARC OSHA

Tetrachloroethylene CNS KID LIV PC YES YES NO

Abbreviations:

CNS Central Nervous System KID Kidney LIV Liver PC Potential Carcinogen

MATERIAL SAFETY DATA SHEET

Grip Glue

15-0003

07/2014

12. **ECOLOGICAL INFORMATION**

Not available Ecological Information:

DISPOSAL CONSIDERATIONS 13.

Recommended methods of disposal: Dispose of according to Federal, State and Local regulations.

EPA Hazardous Waste Number: Cured material is not an RCRA hazardous waste

TRANSPORTATION INFORMATION

U.S. Dept. of Transportation Ground (49 CFR):

Tetrachloroethylene mixture **Proper Shipping Name**

Hazard Class or Division: 6.1 UN 1897 Identification Number Packing group:

Exceptions: Limited quantities (1 gallon or less): Consumer commodity ORM-D

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Tetrachloroethylene mixture

Hazard Class or Division: 6.1 Identification Number UN 1897 Packing group:

Exceptions: Limited quantities (1 gallon or less): Consumer commodity ORM-D

WaterTransportation (IMO/IMDG):

Proper Shipping Name: Tetrachloroethylene mixture

Hazard Class or Division: 6.1 Identification Number UN 1897 Packing group:

Exceptions: Limited quantities (1 gallon or less): Consumer commodity ORM-D

Marine pollutant: Yes

REGULATORY INFORMATION 15.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances

Control Act Inventory

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community CERCLA/SARA 313:

Right-To-Know Act of 1986 (40 CFR 372): Tetrachloroethylene

California Proposition 65: This product contains a chemical known to the State of California to cause

cancer.



Grip Glue

15-0003

07/2014

16. OTHER INFORMATION

Prepared By: C. Alt

Title: Director - Quality & Development

DISCLAIMER: Some of the information presented is from sources other than direct test data on the product itself. The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.