



M4011	Plastic Bottle, 11 fl. oz. 078698119281
M4032	Plastic Bottle, 32 fl. oz. 078698212456

BRAKE FLUID DOT 5

Meets or exceeds Fed. Motor Vehicle Safety Std. No. 116 of 356°F minimum wet boiling point. For occasional driving and special vehicles.

BENEFITS: Does not absorb water

DIRECTIONS: DO NOT MIX WITH DOT 3 OR DOT 4 BRAKE SYSTEMS. DO NOT USE IN ABS BRAKE SYSTEMS. Thoroughly flush entire brake system before installing new DOT 5 fluid. Clean all dirt from around filler plug on master cylinder before removing. FOLLOW VEHICLE MANUFACTURER'S RECOMMENDATIONS WHEN ADDING BRAKE FLUID. REPLACE FILLER PLUG. CHECK FLUID LEVEL ONCE A MONTH. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE.

STORAGE, HANDLING & DISPOSAL: Dispose of in accordance with all applicable government laws.

DANGER: DO NOT REFILL CONTAINER AND DO NOT USE FOR OTHER LIQUIDS. Never wash cylinders or parts with gasoline, kerosene, or oil. Avoid spilling on brake lining or pads or on car finish. May cause skin and eye irritation. Avoid contact with eyes. Wash hands with soap and water properly.

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation develops or persists, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS