

1 Identification

- · Product identifier
- · Trade name: RACING BIO LIQUID POWER AIR FILTER OIL
- Application of the substance / the mixture
 Air filter oil
 Only for proper handling.
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 BUCHER_AG_LANGENTHAL
 MOTOREX-Schmiertechnik

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 1)

Aquatic Acute 2 H401 Toxic to aquatic life.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary s	tatements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P35	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse
	skin with water/shower.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P332+P313 If skin irritation occurs: Get medical advice/attention.

Do NOT induce vomiting. P331

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P391 Collect spillage.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 3)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components: Reg.nr.: 01-2119475514-35-xxxx Hydrocarbons C6-C7, n-alkanes, iso-alkanes, 50-70% cyclenes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 2, H401

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove contaminated clothing immediately.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

(Contd. on page 5)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



safety goggles

us.

(Contd. on page 6)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 5)

	abandad manadia
Information on basic physical and General Information	cnemical properties
Appearance:	
Form:	Fluid
Color:	Dark green
Odor:	Solvent-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	65 °C (149 °F) (DIN EN ISO 3405)
Flash point:	<-20 °C (<-4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	250 °C (482 °F) (DIN 51794)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	7.3 Vol %
Vapor pressure at 20 °C (68 °F):	1.9 hPa (1 mm Hg)
Density at 20 °C (68 °F):	0.781 g/cm³ (6.517 lbs/gal) (ASTM D 4052)
Density at 15 °C:	0.785 g/cm³ (6.551 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	7.1 mm²/s @ 40 °C (DIN 51562-1)
VOC content:	60.0 %
	468.4 g/l / 3.91 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: Can be distilled without decomposing at normal pressure.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid With strong oxidisers.

(Contd. on page 7)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 6)

- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: The product is highly flammable.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability

Biodegradability according to OECD 301 B: >60 % in 28 days

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-classification according VwVwS, 17.05.1999): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

10 -

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 7)

(Contd. on page 9)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

UN-Number DOT, ADR,ADN, IMDG, IATA	UN3295
UN proper shipping name DOT ADR/ADN	Hydrocarbons, liquid, n.o.s. 3295 Hydrocarbons, liquid, n.o.s ENVIRONMENTALLY HAZARDOUS
IMDG IATA	HYDROCARBONS, LIQUID, N.O. (Naphtha (petroleum), hydrotreated ligh MARINE POLLUTANT HYDROCARBONS, LIQUID, N.O.S.
Transport hazard class(es)	
DOT	
1 1 2004 (2.2)	
Class Label	<i>3 Flammable liquids</i> <i>3</i>
ADR/ADN	
Class Label	<i>3 (F1) Flammable liquids</i> 3
IMDG	
₩ ₂	
Class	3 Flammable liquids

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

1 1	2
Label	3
IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR,ADN, IMDG, IATA	11
Environmental hazards: Marine pollutant:	Yes (DOT) Symbol (fish and tree)
Special marking (ADR/ADN):	Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E,S-D B
Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.
/	тот арриосого.
DOT	Special marking with the symbol (fish and tree).
Transport/Additional information: DOT Remarks: ADR/ADN Excepted quantities (EQ)	Special marking with the symbol (fish and
DOT Remarks:	Special marking with the symbol (fish an tree). Code: E2 Maximum net quantity per inner packaging 30 ml Maximum net quantity per outer packaging

-US

(Contd. on page 10)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 9)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

556-67-2 octamethylcyclotetrasiloxane

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

National chemical directories

Components listed or exempted from listing:

TSCA (USA)

DSL/NDSL (CDN)

ENCS/METI (J)

AICS (Aus)

IECSC (CN)

EINECS/ELINCS/NLP (EU)

ECL/KECI (KOR)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Date of preparation / last revision 04/12/2016 / -
- · Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)

Trade name: RACING BIO LIQUID POWER AIR FILTER OIL

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

110_