

Safety Data Sheet
acc. to OSHA HCS

1 Identification

- **Product identifier**
- **Trade name:** AIR FILTER OIL 206
- **Application of the substance / the mixture**
Air filter oil
Only for proper handling.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
BUCHER_AG_LANGENTHAL
MOTOREX-Schmiertechnik

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64745-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	25-50%
Reg.nr.: 01-2119473851-33-xxxx	<ul style="list-style-type: none"> ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336 	

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Remove contaminated clothing immediately.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Consult a physician who will decide on need and method of emptying the stomach.
Do not induce vomiting. Do not take in resorption stimulating agents.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 3)

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Avoid dehydration; when rewetted the resin volume may increase and cause rupture of the packaging as well as of equipment.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Blue

· **Odor:** Solvent-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 82 °C (180 °F) (DIN EN ISO 3405)

· **Flash point:** 12 °C (54 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 0 °C (32 °F) (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 0.0 Vol %

Upper: 6.8 Vol %

· **Vapor pressure at 20 °C (68 °F):** 30 hPa (23 mm Hg)

· **Density at 20 °C (68 °F):** 0.81 g/cm³ (6.759 lbs/gal) (ASTM D 4052)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 5)

- | | |
|---|---|
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | 15.5 mm ² /s @ 40 °C (DIN 51562-1) |
| VOC content: | 50.1 % |
| | 405.4 g/l / 3.38 lb/gl |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Can be distilled without decomposing at normal pressure.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** With strong oxidisers.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
None known. Complete combustion will give carbon dioxide and water.
- **Additional information:** The product is highly flammable.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 6)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-classification according VwVwS, 17.05.1999): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**
 Disposal must be made according to official regulations.
 Discharged containers can contain flammable or explosive vapours.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, ADN, IMDG, IATA | <p style="margin: 0;">UN3295</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · ADR/ADN · IMDG | <p style="margin: 0;">Hydrocarbons, liquid, n.o.s.
 3295 Hydrocarbons, liquid, n.o.s.,
 ENVIRONMENTALLY HAZARDOUS
 HYDROCARBONS, LIQUID, N.O.S.
 (Naphtha (petroleum), hydrotreated light),
 MARINE POLLUTANT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
| <div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class | <p style="margin: 0;">3 Flammable liquids</p> |






(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 7)

· Label	3
· ADR/ADN	
 	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG	
 	
· Class	3 Flammable liquids
· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR,ADN, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR/ADN):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/ADN	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging:

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Trade name: AIR FILTER OIL 206

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Abteilung Produktsicherheit
- **Date of preparation / last revision** 03/22/2016 / -
- **Abbreviations and acronyms:**
 - Flam. Liq. 2: Flammable liquids, Hazard Category 2*
 - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*
 - Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

US