

MOTO GEAR OIL

SAE 10W/30

Multigrade gear oil for motorbikes

Description

MOTO GEAR OIL SAE 10W/30 is a multigrade, synthetic-base gear oil specially tailored to the requirements of motorbikes. First-class base oils and cutting-edge additives ensure optimum lubrication and shiftability.

Advantages

- excellent shiftability at all temperatures
- first-class corrosion protection
- markedly powerful foam inhibition
- optimum lubricating reliability throughout the period of use

Field of application

MOTO GEAR OIL SAE 10W/30 is especially suitable for gears of two-stroke motorbikes equipped with wet clutches as well as for all motorbikes with separate gear lubrication.

Notes

Synthetic Performance

Specifications

API GL4

Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm ³	ASTM D4052	0.861
Viscosity at 40 °C	mm ² /s	DIN 51562-1	76
Viscosity at 100 °C	mm ² /s	DIN 51562-1	11.7
Viscosity index		DIN ISO 2909	148
Pourpoint	°C	ASTM D5950	-30
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.