



MOUNTING SUGGESTIONS:

Harley-Davidson® Softail 2000-2006 One-piece Seat

Hardware: Stock fender screw
Stock rear bracket or Mustang part 78037

Tools needed: Phillips screwdriver
7/16" wrench or nutdriver

These seats will install on the following motorcycles. If your motorcycle is not listed, please contact Mustang for fitment.

- FLST Heritage 2006
- FLSTC Heritage Classic 2000-2006
- FLSTF Fat Boy 2000-2006 and FLSTFSE 2005
- FXST Softail 2000-2005
- FXSTB Night Train 2000-2005
- FXSTS Springer 2000-2005

Removal of stock seat:

One-piece stock seat:

1. Remove the two mounting bolts from each side of the seat. These are not needed to mount the Mustang one-piece seat.
2. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will be used to attach your new Mustang seat.
3. Slide the seat up and back to disengage the front bracket and remove the seat.
4. Remove the stock bracket from the rear of the seat.



Installation of Mustang seat:

1. Mount stock rear bracket (or part 78037) to rear of Mustang seat.
2. Insert welded nose tab into frame mount under tank.
3. Align rear bracket with fender nut and secure the bracket to the fender with the stock screw.

Note: The angles of the steel pan may need to be adjusted slightly to fit your specific bike.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product.

Refers to part numbers: 75049, 75050, 75072, 75073, 75074, 75076, 75077, 75769, 75779, 76057, 76377, 76891