



MOUNTING SUGGESTIONS:

Honda VT750DC Spirit 2001-2007 One-piece Seat

Hardware: Stock side bolts and rubber bushings x 2

Tools needed: Metric Allen wrenches

Note: There are two holes cut into the vinyl on either side of the Mustang seat for installation. This is not a defect.

Removal of Stock Seat:

1. The stock seat is mounted through the seat on both sides with two Allen bolts. Locate these bolts under the handstrap and remove with a metric Allen wrench.



2. Pull out the two rubber bushings from the sides of the seat. These bushings and the Allen bolts will be used to mount your new Mustang seat.

3. Slide the seat back and up to remove it from the fender. The shoulder bolt on the fender is not used to mount your Mustang seat, and can be left in place or removed.

Installation of Mustang Seat:

1. Engage the nose tab of the Mustang seat into the frame receptacle behind the tank.



2. Insert the two stock rubber bushings through the sides of the seat. A small X has been pre-cut in the vinyl. Check to be sure the bushings line up to the seat's brackets and the frame mounting points.

3. Insert the stock Allen bolts into the rubber bushings, through the seat brackets, and into the frame, and secure with an Allen wrench.

Enjoy the comfort and custom look of your new Mustang seat!



Handcrafted in  the USA

Looking for motorcycle seats & backrests? Visit our website.