



MOUNTING SUGGESTIONS:

Honda VF750 Magna 1994-2003 One-piece Seat

Hardware:	Stock rear fender screw White nylon washer
Tools needed:	Metric Allen wrenches

Removal of stock seat:

1. Remove the rear fender screw and set aside. This will be used to mount your new Mustang seat.
2. Remove the two mounting bolts from either side of the seat. These are not used to mount your Mustang seat.
3. Slide the seat back and up to remove from the motorcycle.



Installation of Mustang seat:

1. Engage the front seat bracket into the frame receiver under the tank.
2. The baseplate is designed to clear the plastic side cover tabs. Align the rear bracket with the rear fender mount and position the white nylon washer between the bracket and the fender.
3. Secure the rear bracket with the stock rear screw.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product..

Refers to part number: 75211

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.