



MOUNTING SUGGESTIONS:

Harley-Davidson®

FXR 1982-1994, 1999-2000

One piece, Solo and Passenger Seats

Hardware:	One-piece: Stock hinge bracket or Mustang part 75080	
	Solo seat: Stock hinge bracket	Passenger seat: <i>Optional: 5/16" - 24 x 3/4"</i> slotted bolts (part 78027 – not included)

Tools needed: Phillips screwdriver
1/2" open-end wrench or nutdriver

Removal of Stock Seat:

One-piece:

Remove rear fender screw and set aside. The stock rear fender screw will be used to attach your new Mustang seat. Slide seat back and up to remove.



Two-piece:

1. Unlatch solo and pivot up to expose hinge.
2. Disengage plastic retaining clip on hinge, slide solo back to clear the hinge and remove.
3. Remove rear fender screw and set aside. Loosen two front mounting bolts, and slide passenger seat back and up to remove.

Installation of Mustang Seat:

Solo and Passenger seat:

1. Transfer the hinge bracket from the stock seat to the Mustang solo.
2. Reconnect the hinge to the frame.
3. Install either stock bolts or washers or Mustang part 78027 slotted bolts into fender.
4. Engage slots in front of passenger seat either under the stock washers or into the slotted bolts. Tighten these bolts securely.
5. Align rear tab with the fender mount and secure with stock screw.



One-piece seat with OEM hinge:

1. Transfer the hinge bracket from the stock seat to the Mustang seat.
2. Align rear tab with the fender mount and secure with stock screw.

One-piece seat without using OEM hinge:

1. Bolt Mustang bracket part 75080 (not included) to the fuel tank's rear mounting holes.
2. Engage the front seat bracket into the bracket.
3. Align rear tab with the fender mount and secure with stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



Handcrafted in  the USA

Looking for motorcycle seats & backrests? Visit our website.