



MOUNTING SUGGESTIONS:

Harley-Davidson® Dyna 1996-2005 One-piece Seat

Hardware:	Stock fender screw Mounting bracket 10-32 screws x 2 Small shoulder washer (1996-2003 only)
------------------	--

Tools needed:	Phillips screwdriver
----------------------	----------------------

Removal of stock seat:

One-piece stock seat:

1. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will

be used to attach your new Mustang seat.

2. Remove the handstrap if present.

3. Slide the seat up and back to disengage the front bracket and remove the seat.

1996-2003 pictured



Installation of Mustang seat:

1. Secure rear bracket to back of baseplate with supplied 10-32 screws. Use the set of holes closest to the rear for Dyna Wide Glide, and the other set of holes for all other Dyna models.

2. Insert welded nose tab into frame mount under tank.

3. Align rear bracket with fender nut, add washer (1996-2003 only) between fender and bracket, and secure the bracket to the fender with the stock screw.

Note: The angles of the steel pan may need to be adjusted slightly to fit your specific bike.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product.

Refers to part numbers: 75109, 75111, 75405, 75415, 75439, 75530, 75531, 75532, 75533, 75536, 75746, 76387