



MOUNTING SUGGESTIONS:

Harley-Davidson® Dyna 1991-1995 Solo and Passenger Seat

Hardware:	Stock rear screw 1/4"-20 x 1/2" screws x 2 (solo) Long and short rear bracket (passenger seat) 10/32 x 5/8" screws x 2 (passenger seat)
------------------	--

Tools needed:	Phillips screwdriver
----------------------	----------------------

Removal of Stock Seat:

1. Remove the rear fender screw and set aside. This screw will be used to mount your Mustang seat.
2. Remove handstrap if present.
3. Lift the stock seat up and back to remove from motorcycle.



Note: Mustang solos and passenger seats will not work with stock seats.

Installation of Mustang Seat:

1. If installing the passenger seat with the solo, join the passenger seat to the solo with the supplied $\frac{1}{4}$ " - 20 x $\frac{1}{2}$ " screws and install as a one-piece unit.



2. If installing the passenger seat with the solo, attach the rear bracket to the passenger seat with the supplied 10-32 x $\frac{5}{8}$ " screws. Use the longer bracket for 1993-1995 FXDWG Wide Glides, and the shorter bracket for other models.



3. Engage the nose bracket of the solo seat with the welded frame tab.

4. Align the rear bracket with the fender mount. The bracket may be as much as 1" over the fender mount.
5. Push the rear bracket down and secure it to the fender with the stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



Accept no compromises, choose only quality motorcycle seats & backrests.