



MOUNTING SUGGESTIONS:

Suzuki

800 Volusia '01-04 & C50&T
'05-17 - Solo and Passenger Seat

Hardware:	Solo: Chrome stud bracket White nylon washer Slotted nut	Passenger seat: Stock rear fender screw
Tools needed:	Metric Allen wrench 5/8" wrench	

Removal of stock seat:

1. Remove the rear Allen screw. This will be used to mount your new Mustang seat.



2. Slide the passenger seat back to remove.

3. Remove the rear seat mounting bracket and handstrap.



4. Slide solo back and up to remove.

Installation of Mustang seat:

1. Install the stud bracket to the fender. The stud must be toward the back of the motorcycle. (If missing, this bracket is available as part 78122.)

2. Engage the solo's nose bracket into frame receptacle below tank. Place the nylon washer over the stud, lower the rear solo bracket over the stud, and secure with the slotted nut. **Note: do not overtighten.**

3. Engage the passenger seat's slotted front bracket with the slotted nut.

4. Secure the rear bracket with the stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product.

Refers to part numbers: 75810, 75811, 75812, 75813, 75814, 75815, 76060, 76061, 76062, 76063, 76064, 76065, 79282, 79283, 79284, 79285, 79286, 79287, 79620, 79621, 79622, 79623, 79624, 79625

View [other motorcycle seats & backrests](#) made by [Mustang](#) on our website.