



MOUNTING SUGGESTIONS:

Kawasaki Vulcan 800 1996-2005 Solo and Passenger Seat

Hardware:	Solo seat: White nylon washer x 2	Passenger seat: Stock rear 6mm bolt 6mm x 25mm hex bolt x 2 Spool washer x 2 White nylon washer
Tools needed:	Metric socket and Allen wrenches	

Removal of Stock Seat:

1. Remove rear 6mm bolt and set aside. This bolt will be used to mount your new Mustang seat.

2. Slide the seat back and up to remove. **Note: The seat is often very tight, some force may be necessary.**



3. Remove the center bracket from the fender. If installing a solo alone, these bolts will be used to mount the Mustang solo.

Installation of Mustang Seat:

1. Engage the solo's front bracket into the frame receptacle under the tank.
2. Position one white nylon washer between each of the rear solo brackets and the fender holes



3. If installing solo only, secure the rear solo brackets with the stock bolts. If installing a passenger seat, position the spool washers over the solo brackets and secure using the 6mm x 25mm hex bolts.



4. Align the passenger seat so that the two slotted brackets engage the spool washers. Push the passenger seat fully forward.

5. Position a white nylon washer between the rear bracket and the fender hole and secure the seat with the stock 6mm bolt.

Enjoy the comfort and custom look of your new Mustang seat!



Accept no compromises, choose only quality motorcycle seats & backrests.