



MOUNTING SUGGESTIONS:

Kawasaki Vulcan 900 2006-2018 One-piece Seat

Hardware:	$\frac{1}{4}$ "-20 x $\frac{3}{4}$ " bolt x 2 $\frac{1}{4}$ "-20 x 1" bolt x 2 $\frac{3}{8}$ " spacers x 2 Stock latch pin bracket
Tools needed:	10mm wrench $\frac{7}{16}$ " wrench

Removal of stock seat:

1. Insert ignition key into left side cover and turn clockwise to unlock stock seat.
2. Lift rear of seat up, and pull seat back to remove.



Installation of Mustang seat:

1. Remove the latch pin bracket from the center of the stock seat with a 10mm wrench.
2. **Classic:** Install bracket to Mustang seat using $\frac{1}{4}$ "-20 x $\frac{3}{4}$ " bolts. Tighten securely with a $\frac{7}{16}$ " wrench. **Do not overtighten.**

Custom: Install bracket to Mustang seat using $\frac{1}{4}$ "-20 x 1" bolts, placing $\frac{3}{8}$ " spacers between seat and bracket. Tighten securely with a $\frac{7}{16}$ " wrench. **Do not overtighten.**
3. Slide nose bracket of seat under the gas tank receiver, and push seat all the way forward, then down onto the fender latch.
4. Push the center of the seat down until a click is heard, signifying the seat is locked.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product.

Refers to part numbers: 76126, 76127, 76128, 79416, 79417