



## MOUNTING SUGGESTIONS:

### Honda VTX1800F 2005-2008 Solo and Passenger Seat

<b>Hardware:</b>	<b>Solo seat:</b> Stock 8mm side Allen bolts x 2	<b>Passenger seat:</b> Stock rear 6mm bolt White nylon washer
<b>Tools needed:</b>	6mm Allen wrench 5mm Allen wrench	

#### Removal of Stock Seat:

1. Locate and remove the two 8mm side mount screws using a 6mm Allen wrench. These will be used to mount your Mustang seat.



2. Locate and remove the stock bolt at the rear of the seat using a 5mm Allen wrench.

3. Lift the stock seat up and back to remove from motorcycle. The solo and passenger seat are bolted together and can be removed as a unit.

## Installation of Mustang Seat:

1. If installing solo and passenger seat together, slide the passenger seat's front bracket into the receptacle at the back of the solo and install as a unit. Alternately, solo can be installed alone and the passenger seat can be inserted once the solo is mounted.
2. Slide the solo's front bracket into the frame receptacle under the gas tank.
3. Push the seat forward until the two side brackets are aligned with the motorcycle's side mounts. If the brackets do not line up with the mounts perfectly, they can be slightly adjusted using a screwdriver or similar tool.



4. Insert the two 8mm side mounting screws through the motorcycle and seat mounts. Tighten securely with a 6mm Allen wrench.
5. Ensure the passenger seat is as far forward as possible and the rear bracket aligns with the rear fender mount.



6. Place the white nylon washer under the passenger seat's rear bracket and secure with the stock 6mm bolt. Tighten securely using a 5mm Allen wrench.

**Enjoy the comfort and custom look of your new Mustang seat!**

