



## MOUNTING SUGGESTIONS:

### Yamaha Road Star 1600/1700 '99-15 One-piece, Solo and Passenger Seat

<b>Hardware:</b>	<b>Solo:</b> 1/4"-20 x 3/4" screw x 2 6mm knob	<b>Passenger/One-piece seat:</b> Stock 8mm fender bolt White nylon washer
<b>Tools needed:</b>	6mm Allen wrench 10mm wrench Phillips screwdriver ( <i>for solo/passenger only</i> )	

#### Removal of Stock Seat:

1. Turn ignition key counter-clockwise to release seat latch and remove solo seat.

2. Remove the 8mm stock rear fender screw and remove passenger seat. This screw will be used to mount your Mustang passenger seat.

3. Remove the three 6mm bolts from the fender bracket and remove. Remove the bracket from the fender and replace the three bolts into the fender.



## Installation of Mustang Seat:

*Solo only:*

1. Remove the 6mm knob from under the solo's rear mounting bracket.
2. Position the solo seat onto the motorcycle and push firmly onto the nose to engage the seat into the latch.
3. Mount the solo's rear mounting bracket to the fender hole with the 6mm knob or the stock bolt.



*Solo and passenger seat, or One-piece:*

1. If installing solo and passenger seat, ensure the seats are screwed together securely.
2. Position the seat onto the motorcycle and push firmly onto the nose to engage the seat into the latch.

3. Position the white nylon washer between the rear mounting bracket and the rear fender mount and secure with the stock 8mm mounting bolt.

**Note: To access helmet locks and tool kit, unlatch the front of the seat, lift slightly and pivot a few inches to one side.**

**Enjoy the comfort and custom look of your new Mustang seat!**



Handcrafted in  the USA

Looking for motorcycle seats & backrests? Visit our website.