



MOUNTING SUGGESTIONS:

Harley-Davidson® Softail Deuce 2000-2007 Solo and Passenger Seat

Hardware:	Solo seat: Stock side Allen bolts x 2	Passenger seat: Stock rear bracket 10/32 x 5/8" screws x 2
Tools needed:	Phillips screwdriver SAE Allen wrenches	

Removal of Stock Seat:

1. Remove the rear fender screw.
2. Remove handstrap if present.
3. Lift the stock seat up and back to remove from motorcycle.



Note: Mustang solos and passenger seats will not work with stock seats.

Installation of Mustang Seat:

1. Locate the Allen bolts securing the front of the struts and remove.
2. Remove the spacer washers from between the struts and the frame.



3. Insert the seat's nose bracket into the frame mount behind the gas tank.
4. Lower and align the seat's side brackets between the struts and the frame.
5. Re-insert the stock Allen bolts and tighten securely.
6. If installing passenger seat, remove the stock rear bracket from the stock seat and mount it to the back of the Mustang passenger seat with the supplied 10/32 x 5/8" screws.



7. Slide the front passenger seat bracket into the receiver under the back of the Mustang solo as far as possible.

8. Align rear bracket with fender nut and secure with stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



Handcrafted in  the USA

Looking for motorcycle seats & backrests? Visit our website.