



## MOUNTING SUGGESTIONS:

### Honda VTX1800C 2002-2008 Solo and Passenger Seat

<b>Hardware:</b>	<b>Solo seat:</b> Stock side Allen bolts x 2	<b>Passenger seat:</b> Stock rear acorn nut Chrome spool washer 6mm x 25mm bolt Nylon washer x 2
<b>Tools needed:</b>	6mm Allen wrench 10mm open-end wrench	

#### Removal of Stock Seat:

1. Locate and remove the two side mount screws using a 6mm Allen wrench. These will be used to mount your Mustang seat.



2. Locate and remove the stock acorn nut at the rear of the seat using a 10mm wrench.

3. Lift the stock seat up and back to remove from motorcycle.

## Installation of Mustang Seat:

1. If installing solo and passenger, install one of the nylon washers under the chrome spool washer and secure to the fender with the 6mm x 25mm bolt.
2. Slide the solo's front bracket into the frame receptacle under the gas tank.
3. Push the seat forward until the two side brackets are aligned with the motorcycle's side mounts.



4. Insert the two side mounting screws through the motorcycle and seat mounts. Tighten securely.
5. Slide the passenger seat forward until the rear bracket engages the spool washer bolted to the fender mount.



6. Place the remaining nylon washer under the passenger seat's rear bracket and secure with the stock acorn nut. Tighten securely.

**Enjoy the comfort and custom look of your new Mustang seat!**



View [other motorcycle seats & backrests](#) made by [Mustang](#) on our website.