



## MOUNTING SUGGESTIONS:

**Kawasaki Mean Streak '02-08,  
Suzuki VZ1600 '04 & M95 '05  
Solo and Passenger Seat**

|                  |  |
|------------------|--|
| <b>Hardware:</b> | Stock 6mm bolt x 2<br>Stock fender acorn nut<br>White nylon washer |
|------------------|--|

|                      |            |
|----------------------|------------|
| <b>Tools needed:</b> | 8mm wrench |
|----------------------|------------|

### Removal of stock seat:

1. Locate and remove the two 6mm bolts from each side of the seat, and the rear acorn nut from the fender.
2. Slide seat back and up to remove.



### Installation of Mustang seat:

1. Engage the front bracket of the solo into the frame receptacle under the tank.
2. Insert and secure the two 6mm bolts through the seat brackets and into the frame.
3. Slide passenger seat's front bracket into the receiver in the back of the solo. Push fully forward until rear bracket aligns with the fender mount.
4. Secure the rear bracket to the fender with the stock acorn nut.



Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product.

Refers to part numbers: 75850, 75851, 75852, 75853, 75854, 75855, 79290, 79291, 79292, 79293, 79294, 79295