



Quantum® Hardcoated Polycarbonate
VStream® Windscreen for:
Yamaha® Ténéré 700



N20337 Light Tint, Sport
N20338 Light Tint, Sport-Tour
N20339 Clear, Touring



VStream® Windscreen Patent No. 7,387,328

Thank you for purchasing a National Cycle product. Read these instructions carefully and thoroughly before beginning work. Dealers, if installing this windshield for a customer, please give them this manual upon completion. It contains information needed to properly maintain and use this product.

Description:	VStream® Replacement Windscreen	Model:	2020-Later Yamaha® Ténéré 700
Part Number:	N20337/N20338/N20339	Installation Time:	10 min. Difficulty Level: Easy

CONTENTS OF KIT

ITEM	DESCRIPTION	QTY.
A	VStream Windscreen	1

TOOLS REQUIRED

4mm Hex Key

**ALL OEM FASTENERS
WILL BE REUSED.**



ATTENTION: Special notes and cautionary measures which can prevent damage to the accessory or vehicle.



NOTE: Tips for facilitation of operation, control and adjustment, as well as maintenance work.




Figure 1

PREPARATION

Place motorcycle securely on its sidestand.



All OEM fasteners will be reused.

OEM WINDSHIELD REMOVAL

Figure 1

With a 4mm Hex Key, loosen and remove all four Allen Screws and Washers holding the OEM Windscreen to the mounting bracket.

Screws and Washers will be reused for installation of your new VStream® Windscreen.

WINDSCREEN INSTALLATION

Figure 2

Install the Windscreen onto the motorcycle's mounting hardware and align the mount holes. Reinstall the OEM Allen Screws and Washers.

With a 4mm Hex Key, tighten all four OEM Allen Screws securely. Do not overtighten.

Ride safe and enjoy your new VStream Windscreen!




Figure 2



CLEANING AND MAINTENANCE

To clean the screen, wash with a clean soft cloth and plenty of warm water and, if necessary, a non-abrasive soap such as dishwashing liquid. Flannel or soft chamois make good cleaning cloths. Paint, glue residue or grease removal: Moisten cotton wad with naphtha or turpentine followed by a wash as above.

National Cycle **Shield Wash™** (N1401-01) makes a good daily cleaner and comes with a handy travel-size bottle. Shield Wash is safe for all windshields and helmet visors

Do not clean polycarbonate in hot sun or high temperatures. Do not clean the screen with household glass cleaners. Do not allow brake fluid, alcohol, or strong solvents to contact the screen.

RAIN REPELLENT

Do not use rain protective products made for glass. We recommend National Cycle's **RainZip®** (N1410-01) to keep your windscreen clear in rainy weather.

WARNING

Never ride your motorcycle with loose accessory mounting hardware. Check the hardware for tightness regularly.

Today's motorcycles are built to withstand the moderate loads imposed on them by the foreseeable addition of an accessory(ies). If an accessory(ies) adversely affects your motorcycle's stability, immediately remove the accessory(ies). Do not ride a motorcycle that exhibits unsafe handling traits.

Have experienced service personnel correct any problem before riding with the accessory(ies) installed. For further questions concerning handling problems associated with an accessory(ies), contact your dealer, motorcycle manufacturer, or accessory manufacturer.

Sunlight reflected off the inside curvature of the windscreen can, at certain times of day, cause extreme heat buildup on the motorcycles instruments and possibly even melt them. Exercise care in parking to avoid this. Park your motorcycle facing the sun or place an opaque object over this area.