
## INSTRUCTIONS

NR-220 Getaway & NR-230 Destination


Please read instructions carefully before installation. We recommend this product be installed by a qualified and experienced motorcycle technician. If you are unsure of any of the below directions and/or your ability to correctly and securely install this product, please contact us or your local dealer for help. Below diagrams show typical installation, your motorcycle may be different so please use diagrams as a guide. Make sure your motorcycle is clean and free from dirt, road grime, etc. where the Nelson-Rigg luggage mounts.



With bag sitting on a luggage rack or passenger seat, loosen self fastening straps. With straps passing through "D" ring, slide over your backrest. Pull to tighten and lay the strap back onto itself, connecting the self fastening straps. For the side attachments pass the strap with the male buckle around the luggage rack or frame and reconnect with the female buckle attached to the bag. Make sure the male buckle clicks into place. Repeat this on all 4 straps on the bag. Make sure the bag has little if any movement up, down or left and right before riding. Always recheck mounting before every ride.



The high capacity Destination bag is conveniently divided into 2 distinctive compartments and makes packing your personal items a breeze. A generous lower main compartment for larger items and convenient top storage for items that can be quickly accessed.



In case of inclement weather or even to keep your bag cleaner, use the included waterproof rain cover to protect your bag.

After the bag is completely covered and the bottom bungee wraps around under the bag, secure the rain cover using the side attachment straps. Pass the strap with the male buckle around the luggage rack or frame, lift the rain cover flap and insert the buckle through the slot and reconnect into female buckle under the cover. Fasten the cover flap closed. Repeat on all 4 straps on the bag.



You can access the main compartment via two different ways. From the easy to open zippered top main lid, or from the giant front pocket that folds down for easy access to items packed lower in the bag. One the destination bag only, if more room is needed or you store a taller item, the floor of top section unzips and rolls up making the bag one large storage compartment.



Warning

Read the installation instructions and make yourself familiar with the process of installing the Nelson-Rigg® product(s) on your bike. It is your responsibility to mount the product correctly as outlined in these instructions. Nelson-Rigg® products are intended for use at USA street legal speeds as posted by the individual States. Nelson-Rigg® lugage must not be overloaded. Max carrying capacity is 10 lbs per bag or the maximum load suggested by the manufacturer of the undertained the individual states.

these warnings may resulting, but not limited to: the luggage becoming detached, the product becoming tangled in licit dynamics, reduction in the ability to control the vehicle. The result(s) of could lead to serious injury. Always ride a safety, adhering to the local highway regulations. Always wear a helimet and protective apparel

