



Saddlebag Instructions

RG-020


Please read instructions carefully before installation. We recommend this product be installed by a qualified, and experienced technician. If you are unsure of any of the below directions and or your ability to correctly and securely install this product, please contact us or your local dealer for help. Below diagrams show typical installation, your vehicle may be different so please use diagrams as a guide. Make sure your vehicle is clean and free from dirt, road grime etc. where the this product mounts. It is the riders responsibility to make sure the product is mounted and secure before each use. Loading the bag may result in a change of position, always check for proper mounting position after loading and before each and every ride.




Place Self Fastening straps over seat and level bags. Adjust height of both bags and attach the hook and loop webbing together. Take caution that bag is not on hot or moving parts.




Secure both hooks under the fender and pull the straps tight as shown. Loop the straps thru the "D" ring near each hook.



OPTIONAL STRAPS INCLUDED: If you do not have a plastic dual sport fender, use the 2 supplied straps with loops and wrap around a secure point on the vehicle and insert the strap thru the loop cinching tight. Then follow next step.



Thread the strap from the rear "D" ring or strap with loop thru the buckle at the rear of the bag and pull snug.



Loop front strap around frame or secure point thread thru buckle and pull until tight. Secure all loose end and keep away from moving or hot parts.

Warning:

Read the installation instructions and make yourself familiar with the process of installing the Nelson-Rigg® product(s) on your bike. It is your responsibility to mount the product correctly and securely as outlined in these instructions. Nelson-Rigg® products are intended for use at USA street legal speeds as posted by the individual States. Nelson-Rigg® luggage must not be overloaded. Max carrying capacity is 10 lbs per bag or the maximum load suggested by the manufacturer of the vehicle, whichever is less.

Failure to adhere to these warnings may result in, but not be limited to: the luggage becoming detached, the product becoming tangled in moving parts of the vehicle, unstable vehicle dynamics, reduction in the ability to control the vehicle. The result(s) of could lead to serious injury.

Always ride safely, adhering to the local highway regulations. Always wear a helmet and protective apparel.

