

TYRES TECHNOLOGY

Pioneering innovation to stay ahead of the game.

RADIAL CARCASS CONSTRUCTION

The patented technology enables the structure of both front and rear tyre to be achieved using a radial carcass and a single layer belt made of steel. Depending on the rolling direction of the tyre, the belt is wound circumferentially around the carcass giving an angle close to 0°. The advantages of the use of steel are its extremely high rigidity and the possibility to tune the winding spacing thus differentiating the stiffness distribution from shoulder to crown.



RADIAL CROSS BELTED CONSTRUCTION

The main difference from the bias-belted construction is the structure of the carcass in this case is radial.

This means that its cords are wrapped radially around the tyre, from one bead to the other, giving big advantages in terms of cornering stability, reduced weight and high-speed performance.

BIAS BELTED CONSTRUCTION

The structure consists of a conventional carcass and a belt made of two or more crossed layers. The difference between the carcass and the belt is determined by the different goals they are designed to fulfill and consequently different materials are used in the construction. The belt is made mainly from Aramide and its function is to reduce the dynamic deformation caused by centrifugal forces, while the carcass provides the tyre with its stiffness and load carrying capacity.



CROSS PLY CONSTRUCTION

Also indicated as conventional or x-ply tyre. Depending on the different speed and load specifications, the tyre carcass is structured using two or more overlapping layers. Each layer is made of rubber coated textile cords and the overlap angle is designed in order for the tyre to conform with the required dynamic characteristics.

PIRELLI ORIGINAL
EQUIPMENT &
REPLACEMENT
**LIMITED
WARRANTY
MOTORCYCLE
TYRES**



TYRES TECHNOLOGY

Pioneering innovation to stay ahead of the game.

RADIAL CARCASS CONSTRUCTION

The patented technology enables the structure of both front and rear tyre to be achieved using a radial carcass and a single layer belt made of steel. Depending on the rolling direction of the tyre, the belt is wound circumferentially around the carcass giving an angle close to 0° . The advantages of the use of steel are its extremely high rigidity and the possibility to tune the winding spacing thus differentiating the stiffness distribution from shoulder to crown.



TREAD





ZERO DEGREE STEEL
BELT



be
ing on the
cass
ly high
stiffness

90° CARCASS PLY



rear tyre to be
feel. Depending on the
e
differentiating the stiffness

BEAD



be
g on the
cass
y high
stiffness



BEAD WIRE





RADIAL CROSS BELTED CONSTRUCTION

The main difference from the bias-belted construction is the structure of the carcass in this case is radial.

This means that its cords are wrapped radially around the tyre, from one bead to the other, giving big advantages in terms of cornering stability, reduced weight and high-speed performance.

TREAD







TUBELESS INNER LINER





CARCASS





BIAS BELTED CONSTRUCTION

The structure consists of a conventional carcass and a belt made of two or more crossed layers. The difference between the carcass and the belt is determined by the different goals they are designed to fulfill and consequently different materials are used in the construction. The belt is made mainly from Aramide and its function is to reduce the dynamic deformation caused by centrifugal forces, while the carcass provides the tyre with its stiffness and load carrying capacity.





TREAD



BELT PLY





two or more
determined by the
nt materials are used
unc
arcas

BEAD







CROSS PLY CONSTRUCTION

Also indicated as conventional or x-ply tyre. Depending on the different speed and load specifications, the tyre carcass is structured using two or more overlapping layers. Each layer is made of rubber coated textile cords and the overlap angle is designed in order for the tyre to conform with the required dynamic characteristics.

TREAD








BEAD





CARCASS PLY

A close-up, high-angle shot of the front of a motorcycle. The image focuses on the dual exhaust pipes, which are cylindrical and feature a honeycomb mesh at the top. The fairing above the pipes is a vibrant green color. The motorcycle's frame and other mechanical parts are visible in the background, creating a sense of depth and technical detail.

PIRELLI ORIGINAL
EQUIPMENT &
REPLACEMENT
**LIMITED
WARRANTY
MOTORCYCLE
TYRES**

DISCOVER MORE

Shop for quality Pirelli products on our website.

Learn more about motorcycle tires we have.