Handguard Gauntlet X2

Part # 34458

Installation Instructions



Step 1	Determine the left and right gauntlet. Th on the outside edge of the gauntlet w gauntlet and turn it inside out. This will n	
Step 2	Fasten the hook and loop fastener strap located on the opposite side of the logo. Slide the closed loop over the inside (reservoir cover) of your handguard. See photo 1.	Photo 1
Step 3	Continue sliding the gauntlet onto the handguard until the gauntlet completely covers the handguard. The outside edge of the handguard should touch the outside edge of the gauntlet. See photo 2 and 3.	ERS DSH Dhoto 2
Step 4	Secure the two outside hook and loop fastener straps of the gauntlet in a criss-cross fashion as shown in photo 3.	Photo 3
Step 5	At this point turn the gauntlet right side out. See photo 4.	Photo 4

Handguard Gauntlet X2

Part # 34458

Installation Instructions



Step 6	Overlap and secure the side hook and loop fastener flaps. You have a large area of hook and loop fastener on the side flaps which can be used to adjust the position of the gauntlet by securing in various positions. See photo 5.	Photo 5
Step 7	Secure the handlebar cover by looping the 1" strap through the buckle and tighten around handlebar. The handlebar cover will help to seal any air and or water from entering the inside of your gauntlet. Make sure the all holes are sealed when tightening the strap. Extra strap can be tucked into the gauntlet.	Photo 6
Step 8	Repeat for other side. CAUTION: MAKE SURE THROTTLE AND BRAKE FUNCTION AS INTENDED.	Photo 7
Note!	On the interior outside edge of each gauntlet are sewn in loops. These can be used to secure the gauntlet to a PowerMadd handwrap or any closed loop handguard system.	Photo 8