

LICENSE SUPPORT ADAPTABLE TO KAWASAKI ZX6R 07' -08'

REF : 4456N



- 1- Dismount the back cowl and the original license support.
- 2- Mount the supplied stop light(6) and tight it on the holes (D). Place the wellnuts (3) supplied in the holes (A) of the license support (7). Tight it on the motorcycle using the M6x20 fasteners (1) and M6 washers (2). Place the electrical cables inside the temperature sheath (4) supplied. Tight the sheath with the supplied bridle (5) on the slots (B) and guide it through hole (C) until the cowl interior.
- 3- Electric connection. The stop light supplied incorporates license light; therefore, the original license light connector does not have to be used. Connect the light supplied with the three cables that feed energy to the original stop light. Verify that the light increases intensity while braking.

INSTRUCTIONS TO ASSEMBLE

Material supplied to assemble the license support:

| | DESCRIPTION | QTY |
|---|---------------------------------|------|
| 1 | White M6x20 DIN1001 fastener | 4 |
| 2 | White M6 washer (Ø18 xØ6 x 1,5) | 4 |
| 3 | Wellnut silicone set | 4 |
| 4 | Temperature insulating sheath | 40cm |
| 5 | Plastic bridle | 1 |
| 6 | Stop light | 1 |
| 7 | Support c\black | 1 |
| 8 | Reflector | 1 |
| 9 | Support for reflector | 1 |

