

HUGGER ADAPTABLE TO KAWASAKI Z750S 05-06' / Z750 07-12'

REF: 4524



INSTRUCTIONS TO ASSEMBLE

- 1- Dismount the original chainguards.
- 2- Remove the rear brake line guide off the swing arm. Mount the bracket supplied (1) underneath the guide (2) as the figure shows, using the allen screw M6x15 DIN912 supplied (3). Tight it aligning the bracket with the swing arm.
- 3- Place the wellnuts in the hugger drills.
- 4- Mount the rear hugger using the allen fasteners M6x15 in the chainguard fixation. For the model Z750S use the M6x15 allen fastener in position (5), and the hexagon fastener M6x15 and the washer in position (6). For the model Z750 '07 use the M6x15 allen fastener in position (6), and the hexagon fastener M6x15 and the washer in position (5).
- 5- Adjust the hugger with the tire through the regulation that the iron fittings offer, and tighten them all.
- 6- Check them periodically, and tighten the fixations.
- 7- In case your motorcycle has other accessories, observe that it does not interfere with the hugger.

Material supplied to assemble the hugger:

DESCRIPTION	QTY
M6x15 Allen screws	3
Black M6x15 DIN933 Hexagon fastener	1
Iron fittings (2 nuts incorporated)	1
Wellnuts	4
Black M6 DIN9021 washer	1
Black M6x15 DIN912 Allen screw	1

